

仅供参考用
For reference only

- 两点法 : 0.0 & 50.9 g.cm
- - - 两点法 : 0.0 & 35.9 g.cm
- 两点法 : 0.0 & 105.1 g.cm

| 线条 Line | Model/Winding 型号/卷线 | Voltage 电压 | No Load 无负荷 | | At Maximum Efficiency 最大效率点 | | | | At Maximum Output 最大功率点 | | | | Stall 堵转 | |
|------------|------------------------|---------------|----------------|-------------|--------------------------------|-------------|--------------|------------------|----------------------------|-------------|--------------|--------------|---------------|--------------|
| | | | Current 电流 | Speed 转速 | Current 电流 | Speed 转速 | Torque 扭矩 | Efficiency 效率 | Current 电流 | Speed 转速 | Torque 扭矩 | Output 功率 | Current 电流 | Torque 扭矩 |
| | | | A | rpm | A | rpm | g.cm | % | A | rpm | g.cm | W | A | g.cm |
| — | F140A-NN-16130 | 4.5 | 0.097 | 11050 | 0.392 | 8858 | 10.1 | 52.0 | 0.841 | 5525 | 25.5 | 1.44 | 1.584 | 50.9 |
| - - - | F140A-PN-14150 | 3.0 | 0.068 | 4599 | 0.223 | 3524 | 8.4 | 45.4 | 0.399 | 2300 | 18.0 | 0.42 | 0.730 | 35.9 |
| — | F140A-PN-16130 | 6.0 | 0.093 | 10600 | 0.445 | 8767 | 18.2 | 61.2 | 1.110 | 5300 | 52.6 | 2.86 | 2.127 | 105.1 |

